



POLYPLASTICS CO LTD
18-1 KONAN
2-CHOME
MINATO-KU, TOKYO 108-8280 Japan



Duracon: GH-10L
Acetal Polyoxymethylene (POM), pellets

| 可燃性 | 值 | 测试方法 |
|-------------|---------|----------------------|
| UL 阻燃等级 | | |
| 0.75 mm, NC | HB | UL 94 |
| 1.5 mm, NC | HB | UL 94 |
| 3.0 mm, NC | HB | UL 94 |
| 3.0 mm, NC | HB40 | IEC 60695-11-10, -20 |
| 0.75 mm, NC | HB75 | IEC 60695-11-10, -20 |
| 1.5 mm, NC | HB75 | IEC 60695-11-10, -20 |
| 热性能 | 值 | 测试方法 |
| RTI Elec | | UL 746B |
| 0.75 mm | 50.0 °C | |
| 1.5 mm | 50.0 °C | |
| 3.0 mm | 50.0 °C | |
| RTI Imp | | UL 746B |
| 0.75 mm | 50.0 °C | |
| 1.5 mm | 50.0 °C | |
| 3.0 mm | 50.0 °C | |
| RTI | | UL 746B |
| 0.75 mm | 50.0 °C | |
| 1.5 mm | 50.0 °C | |
| 3.0 mm | 50.0 °C | |